

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
16 December 2004 (16.12.2004)

PCT

(10) International Publication Number  
**WO 2004/109992 A1**

(51) International Patent Classification<sup>7</sup>: **H04L 12/56**,  
12/28, G06F 19/00, A61B 5/00

[NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(21) International Application Number:  
PCT/IB2004/050785

(72) Inventors; and  
(75) Inventors/Applicants (for US only): **KLABUNDE, Karin** [DE/DE]; c/o Philips Intellectual Property & Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE).  
**MUESCH, Guldo** [DE/DE]; c/o Philips Intellectual Property & Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE).

(22) International Filing Date: 27 May 2004 (27.05.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
03101659.5 6 June 2003 (06.06.2003) EP

(74) Agent: **VOLMER, Georg**; Philips Intellectual Property & Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE).


(71) Applicant (for DE only): **PHILIPS INTELLECTUAL PROPERTY & STANDARDS GMBH** [DE/DE]; Stein-damm 94, 20099 Hamburg (DE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,

(71) Applicant (for all designated States except DE, US):  
**KONINKLIJKE PHILIPS ELECTRONICS N. V.**

[Continued on next page]

(54) Title: **METHOD OF CONTROLLING WIRELESS DATA TRANSMISSION BY SWITCHING BETWEEN SHORT-RANGE AND LONG-RANGE RADIO TECHNOLOGIES**



(57) Abstract: The invention relates to a device, in particular a patient monitoring system with a mobile terminal unit (1) for acquiring patient data. The measured data is transferred from the terminal unit (1) via a short-range radio technology (2) (e.g. Bluetooth) to a data monitor (3) arranged at the patient's bedside when the patient is in the vicinity thereof. If necessary, communication can be switched to a long-range radio technology (7) (e.g. WLAN) to ensure interruption-free data transmission while the patient moves around.

BEST AVAILABLE COPY

WO 2004/109992 A1